

# 52X CD-ROM: CD-3002C



**52x max. CD-ROM drive**

**internal 12/8cm CD-ROM disc drive**

(half height form factor)

**IDE/ATAPI interface with UltraDMA 33**

(max. 33 MByte/sec transfer rate)

**128 kByte Cache Memory**

**Tray load mechanism supporting horizontal  
and vertical use**

**Dust protected enclosure**

**Analog- and Digital audio output  
connector**



| Specifications      | 52X CD Reader (CD-3002C)  |
|---------------------|---|
| Data Transfer Rate  | 3000-7800 kByte/s   |
| Access Time         | 120 ms  |
| Cache Memory        | 128 kByte   |
| Mechanism           | motorized Tray load mechanism for horizontal and vertical use   |
| Interface           | IDE / ATAPI   |
| Burst Transfer Rate | PIO mode 4 / Ultra-DMA 33   |
| Audio               | digital-out and line-out (MPC compatible) at the back   |
| Compatibility       | High Sierra, ISO9660, CD-Audio, CD-ROM (mode1 and mode 2), CD-ROM XA, Single- and MultiSession Kodak Photo CD, CD-I (FMV), Video CD, Enhanced Music CD (CD+), MPC Level 3, CD TEXT, CD-RW read (in compliance with MultiRead spec.), PC2001 |
| Available colours   | beige, black, silver  |
| Weight              | 0.74 kg   |
| Dimensions          | 148.2mm x 42mm x 184mm  |

